


Perma-Grip

UMI - Ferrule Specifications

Internally Expanded Permanent Hose Couplings

Ferrule Specifications (Brass) Continued						
Size	UMI Part Number	Competitor Equiv.	Inside Diameter	Fractional Dim.	Hose Range	Weight (lbs.)
2" **	200-230 AA	R2AAS & R2AASS-A	2.469	2-30/64	2-27/64 - 2-30/64	0.47
	200-234 A	R2AS & R2ASS-A	2.531	2-34/64	2-31/64 - 2-34/64	0.47
	200-238 B	R2BS & R2BSS-A	2.594	2-38/64	2-35/64 - 2-38/64	0.47
	200-240*	No Equivalent	2.625	2-40/64	2-39/64 - 2-40/64	0.47
	200-242 C	R2CS & R2CSS-A	2.656	2-42/64	2-39/64 - 2-42/64	0.47
	200-246 D	R2DS & R2DSS-A	2.718	2-46/64	2-43/64 - 2-46/64	0.47
	200-250 E	R2ES & R2ESS-A	2.781	2-50/64	2-47/64 - 2-50/64	0.47
2-1/2" **	250-302 A	R25AS & R25ASS-A	3.031	3-2/64	2-59/64 - 3-2/64	0.68
	250-306 B	R25BS & R25BSS-A	3.094	3-6/64	3-3/64 - 3-6/64	0.68
	250-311 C	R25CS & R25CSS-A	3.172	3-11/64	3-7/64 - 3-11/64	0.68
	250-316 D	R25DS & R25DSS-A	3.250	3-16/64	3-12/64 - 3-16/64	0.68
	250-321 E	R25ES & R25ESS-A	3.328	3-21/64	3-17/64 - 3-21/64	0.68
	250-326 F *	R25FS	3.406	3-26/64	3-22/64 - 3-26/64	0.68
3" **	300-335 AAA	R3AAAS	3.547	3-35/64	3-32/64 - 3-35/64	0.86
	300-340 AA	R3AAS & R3AASS-A	3.625	3-40/64	3-36/64 - 3-40/64	0.86
	300-345 A	R3AS & R3ASS-A	3.703	3-45/64	3-41/64 - 3-45/64	0.86
	300-350 B	R3BS & R3BSS-A	3.781	3-50/64	3-46/64 - 3-50/64	0.86
	300-354 C	R3CS & R3CSS-A	3.844	3-54/64	3-51/64 - 3-54/64	0.86
	300-355 *	No equivalent	3.906	3-58/64	3-55/64 - 3-58/64	0.86
4"	4" ferrules available in stainless steel only. Please see UMI stainless steel ferrule chart for additional information.					
<p>Ferrule weights are approximate. Items marked with an * are special order only. Ferrules are tested and certified to E.I./A.P.I. 1529 and British Standard EN-1361. ** 2", 2-1/2" and 3" ferrules also available in stainless steel.</p>						
<p>Hose range is a general guideline only. Always measure and confirm hose O.D. prior to selecting ferrule. For optimum fit, UMI recommends the hose O.D. be a line-to-line fit up to a 1/32" loose fit to the ferrule I.D.</p>						



Do not mix UMI coupling components with those produced by other manufacturers.

United Metal Industries, Inc.
 (800) 359-6801 • Fax (516) 354-6715 • www.unitedmet.com